

Varioshake VS 15 O - orbital shaker

Order code: **1304.L003061**



Information about product price on demand

Parameters

| | |
|--------------------------|---------------------|
| Device type | Shaker |
| Manufacturer | LAUDA |
| Maximum speed | 300 rpm |
| Note | Digitální zobrazení |
| Dimension of moving base | 450 × 450 mm |
| Max. amplitude | 30 mm |
| Rotational Speed | 20 - 300 rpm |
| Shaking motion | Orbital |
| Maximum load | 15 kg |
| Quantitative unit | ks |

Specifications and features

- Silently operating and universally applicable Orbital Shaker, long-lasting
- User-friendly microprocessor technique
- Excellently applicable for continuous operation
- Universally applicable through the large amplitude, low noise
- Digital shaking frequency readout and setting via LC-display, in steps of 1.0 rpm, gentle start-up
- Remaining time indication through LC display
- RS 232 serial interface for trouble-free data transfer
- Clearly laid out control panel for easy operation
- An a.c. motor with overload protection drives the unit
- Shaking platform made of anodised aluminium
- Compact, low-wear counterbalanced drive mechanism, ensuring high stability and dependability for continuous operation
- Constant speed independent of load
- Housing made of high impact strength polystyrene
- Comprehensive range of accessories

Applications

What counts when growing micro-organisms, cell and tissue cultures is a "reliable colleague" - an indispensable ingredient for successful work in biochemistry, microbiology, biotechnology, bacteriology and virology. Thus, this unit is particularly well-suited for use in laboratories, incubation and moderating rooms in ambient temperatures between +10 and +50 °C.

Optional Accessories:

3953, 3956, 3957, 3958, 3959, 3965, 3966, 3967, 3983, 3984, 3985, 3986,3987, 3988, 3989