



HELAGO-CZ, s.r.o.
Commercial Register maintained by the Regional Court in Hradec
Králové
Section C, File 17879
Kladská 1082
500 03 Hradec Králové 3
Company ID: 25 96 39 61, VAT: CZ 25963961
Phone: 495 220 229, 495 220 394
Fax: 495 220 154
GSM gate: 602 123 096
E-mail: info@helago-cz.cz
Web: http://www.helago-cz.cz

**GP-32K - Industrial Balance, max.
capacity 31kg**
Order code: **0102.GP32K**



Cena bez DPH

3.911,00 Eur

Price with VAT

4.732,31 Eur

Parameters

Type Balances

Industrial Bal. for Heavier Weights

Series

GP

Approval (Verif. ČMI)

NO

Capacity (maximum)

31000 g

Minimum weighing value	0.1 g*
Capacity [kg]	6,1 / 31
Platform [mm]	384 × 344
Capacity / Min weigh. value [kg/g]	6,1 / 0,1 31 / 1
Interface	RS-232C
Specifications	Approval, IP 65, Calibration with an internal mass, Comparator function, Counting function, Animal weighing function, Percent mode function, Density function
Calibration	Internal
Quantitative unit	ks

Balances A&D series GP - IP65 Dust & Waterproof Precision Industrial Balances with internal calibration. Adjustable swing arm display ("S" models with detached display stand also available).

Features:

- Water & Dust Proof IP-65/NEMA4 Compliant
- GLP/GMP/ISO Compliant
- Standard RS-232C Interface
- ID Number
- Density determination
- HI, OK, LO Indicator
- Accumulation of weighing results
- Internal Calibration
- Display Auto Power OFF
- Auto Power ON
- Data Memory
- Time & Date
- Auto Self Checking
- Optional Under hook
- Interval Time Setting
- Auto Re-Zero
- Large Stainless Steel Weighing Pan
- Multiple Weighing Units & Programmable Unit
- Smart Range*
- Bundled with A&D's new WinCT Software

*The display returns to the precision range by pressing the RE-ZERO (tare) key regardless of the tare value.

Options:

- Under hook
- Comparator Output (Relay with Buzzer)/RS-232C/Current Loop
- Analog/Current Loop Output
- Rechargeable Battery