

**MS-70 - Moisture Analyzer**  
Order code: **0105.MS70**



Cena bez DPH  
Price with VAT

6.280,00 Eur  
7.598,80 Eur

Parameters

Type Balances

Series

Approval (Verif. ČMI)

Capacity (maximum)

Moisture Analyzers

MF, ML, MS, MX

NO

71 g

Min. weighing value	0,1
Division [%]	0,001
Interface	RS-232C
Calibration	External
Weighing pan [mm]	Ø 85
Quantitative unit	ks

- Fast and uniform heating with a straight halogen lamp and innovative SRA (Secondary Radiation Assist) technology shorten measurement time
- Standard WinCT-Moisture (for MS-70 & MX-50 only) for easy analyzing mode setting through PC and for real-time graph displaying of moisture content rate change while measuring
- Sodium Tartrate Dehydrate with its stable moisture rate comes standard for accuracy checking
- Optional temperature calibrator, calibration result can be output
- Memory function allows 20 (10 for MF-50, 5 for ML-50) suitable measurement conditions according to sample and 100 (50 for MF-50, 30 for ML-50) measurement result data storage and outputs
- Four choices of measurement programs, Standard, Automatic Complete, Timer, and Manual Mode are selectable
- Clear and easy-to-see, large VFD display shows measurement, setting value, change in moisture content, action status, data number and other important information
- Low maintenance cost assured, thanks to user replaceable halogen lamp without unit downtime with protective chamber for easy clean
- Progress window for heating check
- "Quick Mode" in the measurement program for drying the sample faster by heating the sample at 200°C for 3 minutes.
- Self check function
- Conformity to GLP,GMP,GCP and ISO with date /time ,ID calibration data and check record outputs