

**RT 15 to 15-positions magnetic  
 stirrer with heating**  
 Order code: **1308.3692600**



Cena bez DPH 4.930,00 Eur  
 Price with VAT 5.965,30 Eur

Parameters	
Device type	Magnetic stirrers
Description	Patnáctimístná s ohřevem 580W
Speed [rpm]	0 - 1000
Plate dimensions (w x d) [mm]	270 x 495
Max. volume [l]	0.4l na pozici
Heating capacity [W]	580
Heating	YES
Maximum speed	1000 rpm
Number of positions	15
Quantitative unit	ks

Precise temperature distribution on the heating plate makes it possible to perform series experiments.

- Simultaneously operating stirrers

Number of stirring positions	15
Stirring quantity max. per stirring position (H <sub>2</sub> O)	0,4 l
Stirring position distance	90 mm
Speed deviation of individual stirring positions	5 %
Stirring quantity max. (H <sub>2</sub> O)	6 l

Motor rating input	21,6 W
Motor rating output	5,4 W
Speed range	0 - 1 100 l / min
Stirring bar length max.	30 mm
Heat output	580 W
Heating temperature range	room temp. - 120 °C
Heat control	scale 1 - 10
Speed control	scale 1 - 10
Temperature constancy in medium	2 ±K
Temperature medium max. (dep. on vessel)	70 °C
Set-up plate material	silicone
Set-up plate dimensions	270 × 450 mm
Dimensions (W × H × D)	288 × 65 × 552 mm
Weight	6 kg
Permissible ambient temperature	5 - 40 °C
Permissible relative moisture	80 %
Protection class according to DIN EN 60529	IP 42
Voltage	230 / 115 / 100 V
Frequency	50 / 60 Hz
Power input	600 W
Absolute consistency over sample conditions for the individual samples	
Number of stirring positions	15
Stirring quantity max. per stirring position (H2O)	0.4 l
Stirring position distance	90 mm
Speed deviation of individual stirring positions	0 %
Speed display	LED line
Speed range	0 - 1000 rpm
Stirring bar length min.	25 mm
Stirring bar length max.	30 mm
Heat output	580 W
Heating rate (1 l H2O in H15)	3 K/min
Heating temperature range	Room temp. - 120 °C
Temperature medium max. (dep. on vessel)	70 °C
Heat control	LED
Heat control accuracy	1 ±K
Speed control	10 RPM Steps
Adjustable safety circuit min.	50 °C
Adjustable safety circuit max.	150 °C
Set-up plate material	Aluminium alloy
Set-up plate dimensions	270 x 495 mm
Dimensions (W x H x D)	280 x 60 x 610 mm
Weight	10.5 kg
Permissible ambient temperature	5 - 40 °C
Permissible relative humidity	80 %
Protection class according to DIN EN 60529	IP 40
Voltage	230 / 115 / 100 V
Frequency	50/60 Hz

Power input

620 W