



HELAGO-CZ, s.r.o.
Commercial Register maintained by the Regional Court in Hradec
Králové
Section C, File 17879
Kladská 1082
500 03 Hradec Králové 3
Company ID: 25 96 39 61, VAT: CZ 25963961
Phone: 495 220 229, 495 220 394
Fax: 495 220 154
GSM gate: 602 123 096
E-mail: info@helago-cz.cz
Web: <http://www.helago-cz.cz>

5804 - Centrifuge (without rotor)
Order code: **1309.5804000010**



Cena bez DPH

4.360,00 Eur

Price with VAT

5.275,60 Eur

Parameters

Device type	Centrifuges
Description	High speed centrifuge for medium capacity needs
Max. speed	14000 rpm
Quantitative unit	ks

- Speed, rcf, and radius correction values can be entered by the user
- Values can be changed during centrifugation
- Speed can be set from 200 rpm to maximum speed in increments of 10 rpm
- Selectable program memory for up to 34 individual user programs
- Short-spin key with selectable rotational speed
- Fast-temp function* for rapid cooling of the centrifuge chamber
- "at set rpm" for even more reproducible results
- 10 acceleration and 10 braking ramps for sensitive sample material

Porovnání modelové řady 5804..

	5804	5804 R
Max. power consumption	900 W	1 650 W
Power supply	230 V, 50 - 60 Hz	230 V, 50 - 60 Hz
Cooling	-	refrigerated
Dimensions (W x D x H)	47 x 55 x 34 cm	64 x 55 x 34 cm
Height (with open lid)	74 cm	74 cm
Temperature control range	-	-9 °C to 40 °C
Weight w/o accessories	55 kg	80 kg
Max. RCF	20,913 x g	20,913 x g
Max. RCF with fixed-angle rotor	20 913 x g	20 913 x g
Max. RCF with swing-bucket rotor	4 500 x g	4 500 x g
Max. RCF with plate rotor	2 250 x g	2 250 x g
Speed	200 - 14,000 rpm (10 rpm steps)	200 - 14,000 rpm (10 rpm steps)
Max. capacity	4 x 250 mL/ 2 x 5 MTP	4 x 250 mL/ 2 x 5 MTP
Rotors available	12	12
Acceleration/braking ramps	10/10	10/10
Number of programs	35 user-defined programs	35 user-defined programs
Timer	1 min to 99 min, with continuous run function, short-spin	1 min to 99 min, with continuous run function, short-spin
Noise level	< 62 dB(A)	< 58 dB(A)
Rotor FA-45-6-30 (6x50 mL)	<55 dB(A)	<54 dB(A)
Rotor S-4-104 (4x750 mL)	-	-
Rotor S-4-72 (4x250 mL)	<62 dB(A)	<58 dB(A)