



Information about product price on demand

#### Parameters

Types of safety cabinets

Color

Interior equipment

Quantitative unit

Typ 90 - spodní skříň

Světle šedá

Záchytná vana

ks

- Safe and approved storage of hazardous materials in workrooms
- 90 minutes fire resistance cabinet in accordance with EN 14470-1
- Cylinder locking (suitable for masterkey systems)
- The extraction air inlet is flush with the ceiling of the cabinet
- Earthing link (standard)

#### Operation

- Minimal effort: door opening - easy and safe

#### Drawer

- Remain open in every position
- Interior completely visible - easy and safe access to all containers
- Earthing wire with clamp inside the drawer for used containers (standard)
- Bottom collecting sump sealed by welding, impervious to fluids
- Useable interior height approx. 460 mm
- Load capacity per drawer (evenly distributed load): approx. 50 kg

#### Doors

- Remain open in every position

- Automatic closing of doors and drawers by an integrated thermal release system (fusible link)

**Interior equipment (sheet-steel, plastic laminated)**

- Drawer with bottom collecting sump
- Or wing doors with bottom collecting sump and perforated metal panel

**Cabinet with width of 590 mm**

- Type 90
- Dimensions W × D × H (mm): exterior approx. 590 × 570 × 600, interior approx. 470 × 450 × 500
- Weight: approx. 120 kg