



HELAGO-CZ, s.r.o.
Commercial Register maintained by the Regional Court in Hradec
Králové
Section C, File 17879
Kladská 1082
500 03 Hradec Králové 3
Company ID: 25 96 39 61, VAT: CZ 25963961
Phone: 495 220 229, 495 220 394
Fax: 495 220 154
GSM gate: 602 123 096
E-mail: info@helago-cz.cz
Web: http://www.helago-cz.cz

VBF.196.120-G - Safety Cabinet type 90

Order code: **8101.VBF196120G**



Information about product price on demand

Parameters

Types of safety cabinets

Color

Interior equipment

Quantitative unit

Typ 90 - křídlové dveře

Žlutá

Police

ks

- Safe and approved storage of hazardous materials in workrooms
- 90 minutes fire resistance cabinet in accordance with EN 14470-1 (Type 90)
- Cylinder locking (suitable for masterkey systems)
- The extraction air inlet is flush with the ceiling of the cabinet
- Adjusting aids to compensate for uneven floor
- Earthing link (standard)

Operation

- Smooth, air-damped door closing
- Minimal effort: door opening - easy and safe
- Door closing system outside the storage compartment: increased protection of moving and safety relevant components against corrosion

Wing doors

- 90° opening, interior of the cabinet completely visible

Door open arrest system (optional)

- Holds door open and eases the storage and removal inside the cabinet
- Door open arrest system with an integrated, thermal release system (fusible link), automatic closing of the doors

Interior equipment

- 3 adjustable shelves with inclination and pull-out protection, adjustable in different height in 32 mm - load on one shelf (uniform distributed) approx. 75 kg
- Easily removable bottom collection sump with three-sided lip seal for safe collection of leakage
- 1 perforated metal plate inserted at the bottom of collecting sump

Cabinet with width of 1 200 mm (VBF.196.120)

- Double wing doors
- Dimensions w × d × h (mm): exterior approx. 1200 × 615 × 1968, interior approx. 1050 × 520 × 1740
- Weight: approx. 420 kg
- Bottom collection sump volume 33 l