



Information about product price on demand

#### Parameters

Types of safety cabinets

Typ 30 - křídlové dveře

Quantitative unit

ks

- Detailed description
- Safe and approved storage of hazardous materials in workrooms
- 30 min. fire resistant cabinet in accordance with EN 14470-1 (Type 30)
- Door open arrest system (optional)

- Cylinder locking
- Extraction air inlet on the top
- Earthing link (standard)

### Operation

- Safe, oil damped door closing
- Door closing system outside the storing compartment: increased úrptection of moving and safety relevant components against corrosion

### Wing Doors

- 90° opening, complete visible cabinet interior

### Door open arrest system (optional)

- Holds door open and eases the storage and removal inside the cabinet

### Your safety in the event of fire

- Door open arrest system with an integrated, thermal release system (fusible link), automatic closing of the doors

### Base

- Integrated base (100 mm ground clearance)
- Cabinet can be transported easily with a pallet truck, as the base has a removable faceplate

### Shelves

- Height adjustable (32 mm increments)
- Load capacity per shelf: approx. 75 kg

### Bottom collecting sump

- Easy to remove

### Cabinet with width of 1 200 mm (F30.197.120)

- Double wing doors
- Dimensions W × D × H (mm): exterior approx. 600 × 600 × 1970, Ainterior approx. 530 × 505 × 1 650
- Weight approx. 200 kg
- Bottom collecting sump volume 27 l

Do you want to print the page now?

Hide some parts of page before printing



Print partially

Print the page as you see it now



Print complete page

(this box will not be printed)

Edit before printing

Hover your mouse over some part of page, a red rectangle will appear. Click it to hide the selected content of page.



Print!  Show hidden