



HELAGO-CZ, s.r.o.
Commercial Register maintained by the Regional Court in Hradec
Králové
Section C, File 17879
Kladská 1082
500 03 Hradec Králové 3
Company ID: 25 96 39 61, VAT: CZ 25963961
Phone: 495 220 229, 495 220 394
Fax: 495 220 154
GSM gate: 602 123 096
E-mail: info@helago-cz.cz
Web: <http://www.helago-cz.cz>

**GP-61K - Industrial Balance, max.
capacity 61kg**
Order code: **0102.GP61K**



AD GP-30K

Max 30kg Min 3g e 1g d 0.1g

0.0 g

ON/OFF

CAL

MODE

PRINT

TARE

EMERGENCY STOP

Cena bez DPH	6.640,00 Eur
Price with VAT	8.034,40 Eur

Parameters

Type Balances	Industrial Bal. for Heavier Weights
Series	GP
Approval (Verif. ČMI)	NO
Capacity (maximum)	61000 g
Minimum weighing value	0.1 g
Platform [mm]	384 x 344
Interface	RS-232C
Specifications	IP 65, Calibration with an internal mass, Comparator function, Counting function, Animal weighing function, Percent mode function, Density function
Calibration	Internal
Quantitative unit	ks

Balances A&D series GP - IP65 Dust & Waterproof Precision Industrial Balances with internal calibration. Adjustable swing arm display ("S" models with detached display stand also available).

Features:

- Water & Dust Proof IP-65/NEMA4 Compliant
- GLP/GMP/ISO Compliant
- Standard RS-232C Interface
- ID Number
- Density determination
- HI, OK, LO Indicator
- Accumulation of weighing results
- Internal Calibration
- Display Auto Power OFF
- Auto Power ON
- Data Memory
- Time & Date
- Auto Self Checking
- Optional Under hook
- Interval Time Setting
- Auto Re-Zero
- Large Stainless Steel Weighing Pan
- Multiple Weighing Units & Programmable Unit
- Smart Range*
- Bundled with A&D's new WinCT Software

*The display returns to the precision range by pressing the RE-ZERO (tare) key regardless of the tare value.

Options:

- Under hook
- Comparator Output (Relay with Buzzer)/RS-232C/Current Loop
- Analog/Current Loop Output
- Rechargeable Battery