



Cena bez DPH 1.182,00 Eur  
Price with VAT 1.430,22 Eur

#### Parameters

Device type	Magnetic stirrers
Types of stirrers	Magnetické
Speed [rpm]	100 - 1500
Plate dimensions (w x d) [mm]	180 x 180
Max. volume [l]	10
Heating capacity [W]	1000
Heating	YES
Maximum speed	1500 rpm
Number of positions	1
Quantitative unit	ks

Magnetic stirrer with ceramic heating plate. Bushing according to DIN 12878 for connecting a contact thermometer, e.g. ETS-D5.

**Package includes:**

- C-MAG HS 7
- ETS-D5
- H 16 V Support rod
- H 38 Holding rod
- H 44 Boss head clamp

Number of stirring positions	1
Stirring quantity max. per stirring position (H2O)	10 l
Stirring quantity max. per stirring position (H2O)	10 l
Motor rating input	15 W
Motor rating output	1.5 W
Speed display	scale
Speed range	100 - 1500 rpm
Stirring bar length max.	80 mm
Heat output	1000 W
Heating rate (1 l H2O in H15)	5 K/min
Heating temperature range	50 - 500 °C
Heat control	LED
Heat control accuracy	10 ±K
Speed control	scale 0 - 6
Fixed safety circuit	550 °C
Connection for ext. temperature sensor	ETS-D5
Set-up plate material	ceramic
Set-up plate dimensions	180 x 180 mm
Dimensions (W x H x D)	220 x 105 x 330 mm
Weight	5 kg
Permissible ambient temperature	5 - 40 °C
Permissible relative humidity	80 %
Protection class according to DIN EN 60529	IP 21
Voltage	230 / 120 / 100 V
Frequency	50/60 Hz
Power input	1020 W