

HELAGO-CZ, s.r.o. Commercial Register maintained by the Regional Court in Hradec Králové Section C, File 17879 Kladská 1082 500 03 Hradec Králové 3

Company ID: 25 96 39 61, VAT: CZ 25963961 Phone: 495 220 229, 495 220 394

Fax: 495 220 154 GSM gate: 602 123 096 E-mail: info@helago-cz.cz Web: http://www.helago-cz.cz VBFT.SL+4Z - Width 1 200 mm, combinated doors Order code: **8101.VBFT.SL+4Z** 



Information about product price on demand

**Parameters** 

Types of safety cabinets

Color

Interior equipment

Quantitative unit

Typ 90 - kombinované dveře

Světle šedá

4 zásuvky + 4 výsuvné police

ks

- Detailed description
- Combi-Cabinet for flammable liquids, acid and alkalis
- Safe and approved storage of hazardous materials in workrooms
- 90 minutes fire resistance cabinet in accordance with EN 14470-1
- Cylinder locking (suitable for masterkey systems)
- The extraction air inlet is flush with the ceiling of the cabinet
- Adjusting aids to compensate for uneven floor
- Earthing link (standard)

## Operation

- Smooth, air-damped door closing
- Minimal effort: door opening easy and safe
- Door closing system outside the storage compartment: increased protection of moving and safety relevant components against corrosion

## Doors

- 90° opening, interior of the cabinet completely visible
- Less depth open, space saving, protection by vertical anti-trapping door strip

#### Door open arrest system (standard)

- Holds door open and eases the storage and removal inside the cabinet
- Door open arrest system with an ingrated, thermal release system (fusible link), automatic closing of the doors

# Interior equipment

## **Drawers (for flammable liquids)**

- High storage capacity (see table), fully extractable, smooth running
- Sealed by welding, impervious to fluids
- Load capacity per drawer (evenly distributed load): approx. 25 kg

#### Shelves (for flammable liquids)

- 3 adjustable shelves with inclination and pull-out protection, adjustable in different height in 32 mm load on one shelf (uniform distributed) approx. 75 kg
- 1 perforated metal plate incerted at the bottom of collecting sump
- Easily removable bottom collection sump with three-sided lip seal for safe collection of leakage

### Pull-out shelves (for acid and alkalis)

- Load capacity per drawer (evenly distributed load): approx. 25 kg
- Capacity: approx. 15 litres

#### Cabinet with width of 1 200 mm

- One wing door and one folding door
- Dimensions W  $\times$  D  $\times$  H (mm): exterior approx. 1 200  $\times$  615  $\times$  1 968 mm, interior approx. 1 050  $\times$  520  $\times$  1 740 mm
- Weight: approx. 420 kg

Do you want to print the page now? Hide some parts of page before printing



Print partially

Print the page as you see it now



Print complete page

(this box will not be printed)

Edit before printing

Hover your mouse over some part of page, a red rectangle will appear. Click it to hide the selected content of page.



Print



Show hidden