

F30.60.110-2S - Width 1 100 mm, 2× drawers

Order code: **8101.F30601102S**



Information about product price on demand

Parameters

Types of safety cabinets	Typ 30 - spodní skříň
Color	Světle šedá
Interior equipment	Zásuvky vč. záchytné vany
Quantitative unit	ks

- Safe and approved storage of hazardous materials in workrooms
- 90 minutes fire resistance cabinet in accordance with EN 14470-1
- Cylinder locking (suitable for masterkey systems)
- The extraction air inlet is flush with the ceiling of the cabinet
- Earthing link (standard)

Operation

- Minimal effort: door opening - easy and safe

Drawer

- Remain open in every position
- Interior completely visible - easy and safe access to all containers
- Earthing wire with clamp inside the drawer for used containers (standard)
- Bottom collecting sump sealed by welding, impervious to fluids
- Useable interior height approx. 460 mm
- Load capacity per drawer (evenly distributed load): approx. 50 kg

Doors

- Automatic closing of doors and drawers by an integrated thermal release system (fusible link)

Interior equipment (sheet-steel, plastic laminated)

- Drawer with bottom collecting sump
- Or wing doors with bottom collecting sump and perforated metal panel

Cabinet with width of 1 100 mm / 1 400 mm

- Type 30
- Dimensions W × D × H (mm): exterior approx. 1 100 × 550 × 600 / 1 400 × 550 × 600, interior approx. 980 × 445 × 510 / 770 × 445 × 510, 470 × 445 × 510
- Weight: approx.120 kg (width 1 100 mm) / 140 kg (width 1 400 mm)