



Cena bez DPH 1.588,00 Eur

Price with VAT 1.921,48 Eur

Parameters

Inner dimensions (w x d x h) [mm] 583 x 500 x 468 [mm]

Ext. dimensions (wxdxh) 600 x 509 x 610 [mm]

Quantitative unit pcs

- Detailed description

Effective sterilization 254nm ultraviolet lamp and Fluorescent lamp

- Adjustable UV-timer for precise control of decontamination
 - The variable digital timer for UV exposure with detail settings by second. (Delay OFF : Max. 30min)
 - Long life (Up to 8,000 hour) UV lamp
- Anti-glare fluorescent lamp is installed on the center ceiling of the work space area, minimizing shadows and relieves eye strain

User-Friendly Control System

- Microprocessor-based control system
- Bright and vivid VFD display with responsive touch buttons
- Easily indicating the total use time and operating time on the screen

A reliable interlock safety system

- An audible alarm for product and sample protection against UV over exposure
- For safety UV-opaque and resistant 99.99%, thick acryl front, back and sides

- Automatic UV lamp safety shut OFF, in case the door is opened, which prevents accidental UV exposure
- 304 grade stainless steel work surface - Highly durable and rust free work zone, made for easy cleaning
- Self-protection against over-current

Do you want to print the page now?

Hide some parts of page before printing



Print partially

Print the page as you see it now



Print complete page

(this box will not be printed)

Edit before printing

Hover your mouse over some part of page, a red rectangle will appear. Click it to hide the selected content of page.



Print!



Show hidden