



HELAGO-CZ, s.r.o.
Commercial Register maintained by the Regional Court in Hradec Králové
Section C, File 17879
Kladská 1082
500 03 Hradec Králové 3
Company ID: 25 96 39 61, VAT: CZ 25963961
Phone: 495 220 229, 495 220 394
Fax: 495 220 154
GSM gate: 602 123 096
E-mail: info@helago-cz.cz
Web: <http://www.helago-cz.cz>

SW-60KM - Super Washdown Scale IP69K, max. capacity 60kg
Order code: **0103.SW60KM**









Více obrázků

Cena bez DPH

2.820,00 Eur

Price with VAT

3.412,20 Eur

Parameters

Type Balances

Platform Balances

Series

SW

Approval (Verif. ČMI)

NO

Capacity (maximum)

60000 g

Minimum weighing value

5 g

Platform [mm]

300 × 380

Specifications

IP 69K, Comparator function, Counting function

Calibration

External

Quantitative unit

ks

- Detailed description

Scales A&D SW series - super washdown scales IP69K, maximum resistance to hostile environments. Maintaining hygienic facilities is imperative in the food-processing industry, and the sanitary requirements of governments and companies are becoming increasingly strict all around the world. The SW Series of IP69K-rated Super Washdown Scales is ideally constructed for heavy-duty cleaning with high-pressure (~ 10,000 kPa) and high-temperature (~ 85 °C) water, as well as for long-term use in harsh environments.

SW series:

SW-capacity KS - weighing pan size 250 × 250 mm

SW-capacity KM - weighing pan size 300 × 380 mm

SW-capacity KL - weighing pan size 390 × 530 mm

Note: The scales are also available in the metrology verifiable version. These scales are at the end of the code designation "EC".

Features:

- Ultimate protection against the effects of condensation as well as water – both IP69K and IP68 compliant
- Streamlined construction for easy cleaning of food-processing residues
- Stainless steel weighing pan, frame and load cell*
- Rugged and adjustable (0°, 30°, 60° or 90°) indicator bracket
- Touch sensitive capacitive keys to prevent damage from sharp objects
- Auto-tare function to facilitate consecutive check weighing
- Counting mode function
- Bright, multicolored LED display with 5-step comparator lamps
- Auto power off function
- Three sizes of base units, which are also available separately
- Pole stand attachable to either the short or long side of the platform
- The display unit available separately as an IP69K indicator for high pressure washdown

* Weighing pan and frame SUS304, Load cell SUS630

Options:

- Sealed lead acid rechargeable battery (6 V, 4 Ah)
- RS-232C + comparator relay output
- RS-422/485 interface

* RS-232C and RS-422/485 cannot be used at the same time.

* SW series is not IP69K compliant with RS-232C or RS-422/485

Do you want to print the page now?

Hide some parts of page before printing



Print partially

Print the page as you see it now




Print complete page

(this box will not be printed)

Edit before printing

Hover your mouse over some part of page, a red rectangle will appear. Click it to hide the selected content of page.



Print!  Show hidden