

**Workbench 1500 × 650 × 700 to 920 -
height adjustable centrally handle, 2x vice
carpenter diagonally**
Order code: 8008.1104101-HK



Adjustable height
700 - 920 mm

Information about product price on demand

Parameters

Dimensions [mm]

1 500 × 650 × 700 - 920

Height	Centrally adjustable (handle)
Equipment	2x vice carpenter, diagonally
Working place	2
Quantitative unit	ks

Certified (GS certificate) universal workbench for a variety of uses with height-adjustable work surface. Height adjustment is performed centrally using a crank.

- working desktop beech piedroit, thickness 45 mm, longitudinal sides reinforced to 100 mm
- metal legs steel profile 60 × 60 mm, powder coated finish, height rectification with antislip finish
- 2x carpenter vise, easy disassembly and ability to store to rootstocks, vices placed diagonally
- VarioGrip layer on vice jaw for non-slip workpiece gripping, can be complemented with a counterpart from the same material



VarioGrip insert - a counterpart to the jaw

- 2x aluminium guide profile (always throughout the longer side of the table) for mounting of other accessories such as:
 - sliding pad beneath a metal vise
 - sliding pad for scroll saw cutting
 - sliding pad for bevel
 - sliding pad for smaller electric chain saw
 - sliding stop for fixing the workpiece clamped in a carpenter vise



Pad with metal vise



For scroll saw cutting



Bevel



Sliding stop

- All quickly fixed at any location via quick release mechanism
- Option of additional boxes with basic tools for working with wood, paper, electronics
- Possibility of covering the table with plastic pad of 6 mm thickness for works polluting beech boards, eg. clay modeling
- **GS certificate „Geprüfte Sicherheit“ - tested safety**



Tool kit - wood



Tool kit - electronics



Tool kit - paper



Cover plate for working top

Overall dimensions of the bench without accessories: **1500 x 650 x 700 - 920** (w x d x h) [mm]