

U8557160 - Demo Multimeter

Order code: **5401.1017895**



Cena bez DPH

995,00 Eur

Price with VAT

1.203,95 Eur

Parameters

Devices - filter

Analog measuring instruments

Measuring range	0,1 - 600 V AC/DC, 0,1 mA - 10 A AC/DC
Quantitative unit	ks

Electronic meter featuring a double scale for analogue measurement of current and voltage in demonstration experiments. It can handle measurements of current and voltage values and also allows the zero point to be set up in the centre of the scale for measurement of DC quantities. Switching between measuring ranges does not break any circuits connected to the equipment. This means it is possible to carry out measurements on voltage converters, for example, without causing induction surges. Resistance R, conductance G, impedance Z and admittance Y can easily be determined as quotients of current and voltage measurements thanks to the non-interrupting switch capability without the need to change the wiring. This equipment is protected by fuses and authorised for making measurements in circuits directly connected to the low-voltage mains via plugs (CAT II), i.e. for measurements on house-hold appliances, for example. The current measuring ranges are resistant to long-term overloading up to 10 A. The meter is suitable for use as a free-standing instrument or for setting up in training panel frames.

Technické parametry:

Voltage ranges:	0,1 - 600 V AC/DC, 9 rozsahů
Current ranges:	0,1 mA - 10 A AC/DC, 11 rozsahů
Overload protection:	600 V dlouhodobě ve všech napěťových rozsazích 10A dlouhodobě ve 3 A a 1 A rozsahu
Measuring category:	CAT II: 600 V
Connectors:	4 mm bezpečnostní zdířky
Fuses:	2× FF10A/ 600 V (10 × 38 mm)
Power supply:	1× 1,5 V baterie, AA IEC LR6
Automatic cut-off after:	45 min ± 10 min
Scale length:	160 mm
Dimensions:	259 × 297 × 125 mm
Weight:	1,7 kg