



Cena bez DPH

606,00 Eur

Price with VAT

733,26 Eur

Parameters

Pumping rate [l/min]

11,6

Threshold pressure [kPa]

<10

Vacuum pump

Diaphragm

Quantitative unit

ks

- Detailed description

This standard duty diaphragm pump model is a high performance and easy-to-use solution for small benchtop desiccators as it has a small footprint. With a total weight of 2.3 kg it is also portable. Further this model also provides a low sound level during operation with below 45 dB (A).

This package also includes a hydrophobic in-line filter and a silicone vacuum hose for quick connection to your application.

Technical Data

- Number of heads / stages: 2/1
- Max. pumping speed at 50 Hz in m³/h (l/min): 0.7 (11.6)
- Ultimate pressure in mbar (Torr): < 100
- Wired for: 90 to 260V AC /18V DC
- Intake connection: Hose nozzle DN 6
- Exhaust connection: Hose nozzle DN 6, w/exhaust silencer (removable)
- Sound level (dB): < 45
- Dimensions (W/D/H) in mm: 144/127/196
- Motor voltage: 18 VDC
- Operating temperature in °C: 10 to 60 °C
- Weight kg (lbs): 2.3 (5.1)

Do you want to print the page now?

Hide some parts of page before printing



Print partially

Print the page as you see it now



Print complete page

(this box will not be printed)

Edit before printing

Hover your mouse over some part of page, a red rectangle will appear. Click it to hide the selected content of page.



Print!



Show hidden