

HELAGO-CZ, s.r.o. Commercial Register maintained by the Regional Court in Hradec Králové Section C, File 17879 Kladská 1082 500 03 Hradec Králové 3

Company ID: 25 96 39 61, VAT: CZ 25963961

Phone: 495 220 229, 495 220 394

Fax: 495 220 154 GSM gate: 602 123 096 E-mail: info@helago-cz.cz Web: http://www.helago-cz.cz

412021 - Diaphragm pump MPC 090 E - for chemical applications

Order code: **8010.412021**



Cena bez DPH 912,00 Eur
Price with VAT 1.103,52 Eur

Parameters

Pumping rate [l/min] 1,7
Treshold pressure [kPa] <10

Vacuum pump Diaphragm

Quantitative unit ks

Diaphragm pumps for chemical applications - type MPC - are chemically compatible and resistant to aggressive solvents and acid vapors which are common in laboratories. The diaphragm is made out of PTFE. The pump and connection heads are carbon fiber reinforced. Their electrical conductivity prevents electrostatic charging and minimizes the risk of gas mixture igniting inside of the pump.

The diaphragm pump MPC 090 E is a one-stage pump with mounted separator with manometer and metering valve led. It is compact and functional. Maintenance and service are quick and easy to carry out. The pump operates extremely quietly.

The diaphragm pump MPC 090 E is designed for:

- Conveying and compressing neutral and aggressive gases and vapors
- Generation of vacuum up to an ultimate pressure
- Use in physical and chemical laboratories and in the field

Scope of delivery:

- 1-head chemical diaphragm pump
- integrated motor protection switch
- hose nozzle DN 6 for hose inner diameter 6 mm
- vibration isolating feet
- external power supply and AC/DC converter power pack with CEE, UK & US adapters

Technical Data

- Number of heads / stages: 1/1
- Max. pumping speed at 50 Hz in m³/h (l/min): 1 (1.7)
- Ultimate pressure in mbar (Torr): < 100
- Wired for: 90 zo 260V AC / 18V DC
- Intake connection: Hose nozzle DN 6
- Exhaust connection: Hose nozzle DN 6
- Sound level (dB): < 45
- Dimensions (W/D/H) in mm: 144/198/244
- Weight kg (lbs): 2.7 (6)