

HW-200KCEP - Platform Scale ATEX
Order code: **0103.HW200KCEP**



Cena bez DPH

2.853,00 Eur

Price with VAT

3.452,13 Eur

Parameters

| | |
|------------------------|---|
| Type Balances | Platform Balances |
| Series | HV-CEP, HW-CEP |
| Approval (Verif. ČMI) | NO |
| Capacity (maximum) | 220000 g |
| Minimum weighing value | 20 g |
| Platform [mm] | 390 × 530 |
| Specifications | IP 65, Comparator function, Counting function, ATEX |
| Calibration | External |
| Quantitative unit | ks |

- Affordable selection of capacities and resolutions for excellent explosion protection
- High-speed measurement—response within 1 second (for the HV-CEP series)*¹
- Multi-colored 5-step LED comparator lights
- Auto-tare and negative comparison functions realizing "take-away" check weighing
- Highly-visible, LCD display (26 mm character height) with white backlight
- Quick and easy settings using the alphanumeric keypad
- Key lock function to prevent operators from making changes to the scale settings
- IP65 dust & waterproof base unit with a stainless steel (SUS430) pan
- Adjustable response characteristics depending on the degree of drafts and vibrations at the location
- Display hold function
- Counting mode function
- Accumulation (M+) function
- Approx. 1,500 hours of operation with four D batteries*²
- Auto power OFF function to save battery power
- Display angle adjustable to five levels

*1 Time required for the last digit to settle (the stabilization mark will be lit one second after), which is subject to the weighing environment, response characteristic setting and how the target object is placed.

*2 With LED and backlight OFF (or approx. 1,000 hours with LED and backlight ON). The batteries to be used are specified: DURACELL MN1300, ENERGIZER E95, or Panasonic LR20 (XJ).