

## **EUROSTAR 200 control - Overhead Stirrer**

Order code: **1307.3992000**



Cena bez DPH

4.150,00 Eur

Price with VAT

5.021,50 Eur

Parameters

Device type

Overhead stirrers

Speed [rpm]

9/30 - 400/2000

Max. volume [l]

100

Quantitative unit

ks

Extremely powerful laboratory stirrer for highly viscous applications and intensive mixing for quantities up to 100 l (H<sub>2</sub>O). It is designed with a removable wireless controller and a digital TFT display. It automatically adjusts the speed through microprocessor controlled technology within the speed range of 0/6 - 2000 rpm (two speed ranges). The stirrer comes equipped with a RS 232 and a USB interface to control and document all parameters. An integrated torque trend display is provided for the measurement of viscosity changes. Safety circuits installed ensures automatic cut-off in an anti-stall or overload conditions. Continuous comparison of shaft speed to desired speed is maintained and variations are adjusted automatically. This guarantees a constant speed even with changes in viscosities of the sample.

- Multilingual TFT display
- Programmable functions
- Integrated temperature measurement
- Interval operation
- Timer function
- Adjustable safety circuit
- Locked function
- Infinitely adjustable speed
- Push-through agitator shafts
- Overload protection
- Short-term overload operation
- Slim casing
- Quiet operation
- Error code display
- H 67.60 temperature sensor and WH 11 WiCo holder included in delivery