

**Rotor FA-45-6-30, incl. rotor lid, for 6 ×  
15/50 mL conical tube**  
Order code: **1309.5820715006**



Cena bez DPH

2.536,00 Eur

Price with VAT

3.068,56 Eur

Parameters

Device type

Accessories

Quantitative unit

ks

- High-speed rotor for applications in tubes from 5 - 50 mL<sup>1)</sup>
- Max. speed 20,133 × g (12,100 rpm) in Centrifuge 5810 R or 16,639 × g (11,000 rpm) in 5804/5804 R/5810<sup>2)</sup>
- Eppendorf QuickLock rotor lid for fast lid locking
- Aerosol-tight<sup>3)</sup> for safe centrifugation of hazardous samples
- Low rotor weight (3.2 kg) for easy lifting
- Anodized aluminum for high chemical resistance
- 45° borehole angle minimizes pellets smear
- Rotor, lid and adapters are autoclavable (121 °C, 20 min)
- <sup>1)</sup> Please note that a software upgrade may be necessary for older centrifuges when using this rotor. Please contact your local Eppendorf organization or dealer for further information.
- <sup>2)</sup> Rotors F-34-6-38 and FA-45-6-30 maintain 4 °C at 11,000 rpm
- <sup>3)</sup> Aerosol-tightness tested by Public Health England, Porton Down, Great Britain