



Cena bez DPH	3.142,00 Eur
Price with VAT	3.801,82 Eur

Parameters

Type Balances	Industrial Bal. for Heavier Weights
Series	GF-M
Approval (Verif. ČMI)	NO
Capacity (maximum)	8200 g
Minimum weighing value	0.01 g
Interface	RS-232C, USB

Specifications	IP 65, Comparator function, Counting function, Animal weighing function, Percent mode function, Under hook
Calibration	External
Weighing pan [mm]	270 × 210
Quantitative unit	ks

- Detailed description

Features

- IP65 dust and waterproof
- Impact shock detection (ISD) providing feedback to prevent damage to the weight sensor*¹
- Flow rate display (FRD) that makes calculating and recording flow rates easier and more accurate*²
- Shock logging function that records up to 50 adverse impact loads with a timestamp for later inspection
- Cushioning under the weighing pan to mitigate impact shocks significantly
- Flow rate comparator that indicates whether the flow rate is within the designated limits
- Tare memory function that saves the tare value in non-volatile memory
- Automatic self calibration in response to temperature changes or according to set schedules (GX-M)
- Automatic minimum weight calculation with either ECL or an actual, external weight
- Alert function to ensure that the measured quantity is not smaller than the set minimum weight
- Selectable response characteristics for trading weighing speed for higher display stability or vice versa
- User access control (UAC) that password-protects the balance from misuse
- GLP/GMP/GCP/ISO compliant output to meet documentation requirements
- Universal Flexi Coms (UFC) to customize printout content and layout *³
- Gross/Net/Tare output
- Data memory function to save weighing results, calibration results, unit masses to be used in counting mode, etc., in the device itself
- Counting mode with the Automatic Counting Accuracy Improvement (ACAI) function
- Percent mode function for target weighing or checking sample variation
- Animal weighing (average & hold) function for weighing moving objects
- Statistical calculation function (SCF) to facilitate the analysis of measurements
- Five-level comparator function with buzzer
- Auto power ON and OFF functions
- Density determination function
- Underhook for weighing a magnetic material as well as measuring density

*1 Patented

*2 For graphing weight and flow rate changes in real time, download WinCT-FRD here

*3 For editing and sending UFC setting commands, download WinCT-UFC here

Do you want to print the page now?

Hide some parts of page before printing



Print partially

Print the page as you see it now



Print complete page

(this box will not be printed)

Edit before printing

Hover your mouse over some part of page, a red rectangle will appear. Click it to hide the selected content of page.



Print!  Show hidden