

GC-30K - Counting Scale

Order code: **0106.GC30K**



Cena bez DPH 1.052,00 Eur

Price with VAT 1.272,92 Eur

Parameters

Type Balances	Counting Scales
Series	GC
Approval (Verif. ČMI)	NO
Capacity (maximum)	30000 g
Minimum weighing value	5 g
Interface	RS-232C
Specifications	Comparator function, Counting function
Calibration	External
Weighing pan [mm]	300 × 210 mm

Features

- Automatic Item Search (AIS)*¹ to instantly find a desired unit weight
- Large internal memory to store data for up to 1,000 items
- WinCT-Counting (freeware) for easy management of item data
- Unit weight backup
- Memory capacity extension using a MicroSD card
- Three reverse-backlit LCD displays for count, weight, and unit weight data, and one OLED information display
- Information display also acting as a simplified guide for internal settings
- Diverse methods of unit weight setting
- Unit weight entry navigator
- Selectable power sources including mobile battery via USB cable
- Separable display unit
- RS-232C interface that supports digital connection with an A&D balance/scale
- Expanded scope of application using the AD-8561 series of Multi-Interfaces (sold separately)
- Comparator function with highly-visible LED traffic lights and buzzer
- Automatic Counting Accuracy Improvement (ACA)
- Adjustable response characteristics
- Stabilization of approx. 1 second (typical)*²
- Universal Flexi Coms (UFC) to customize printout content and layout
- Auto power ON and OFF functions
- Password lock and key lock functions
- External input terminal

*¹ Patent pending

*² By default settings, the stabilization time is approx. 1.6 seconds.

External Input/Output

RS-232C interface

Multi-Interfaces (optional)

Options

GC-08: Extension cable (2 m)

GC-14: Bracket for AD-8561 and vable

Accessories

AD-8561-MI02: Multi-Interface incl. USB (Type micro B)

AD-8561-MI04: Multi-Interface incl. Terminal (4-pin) block

AD-8561-MI05: Multi-Interface incl. Terminal (7-pin) block

AD-8561-11: Terminal block cover*³

AX-KO1371-200: Crossover RS-232C cable (2 m)

AX-KO7215-150: USB cable for power supply (1,5 m)*⁴

*³ Provided as standard for the AD-8561-MI05 and can also be used for the AD-8561-MI04

*⁴ Provided as standard for the GC series

Model		GC-3K	GC-6K	GC-15K	GC-30K
Minimum unit weight* ⁵	Normal mode	0,1 g	0,2 g	0,4 g	1 g
	Fine mode	0,005 g	0,01 g	0,02 g	0,05 g
Capacity		3 kg	6 kg	15 kg	30 kg
Readability		0,0005 kg	0,001 kg	0,002 kg	0,005 kg

Number of samples

5, 10, 25, 50, 100, or an arbitrary number of pieces

Weighing pan

310 mm × 210 mm

*⁵ Selectable by internal setting