

## WIC 2 | Walk-in-chambers for Stability Testing and Storage

Order code: **2103.9800012**



Information about product price on demand

### Parameters

Humidity range [%rH]	20...90
Temperature range [°C]	10...50
Inner dimensions (w x h x d) [mm]	2400 x 2270 x 3400
Series	WIC
Quantitative unit	ks

### Benefits

- Stable and uniform environment
- Fully complies with Pharma regulations (ICH)Equipment
- Longevity - corrosion resistant

- Ease of operation
- Environmental friendly refrigerant with GWP value 547
- Maintenance possible with the least possible disruption to the climate conditioning
- Perfectly meets requirements in Pharma industry

## **IMPORTANT CHARACTERISTICS**

- Relative humidity accuracy of  $\pm 2.5\%$
- Temperature accuracy of  $\pm 1.5^{\circ}\text{C}$
- Duct work for proper distribution of air
- Highly insulated room panels with U value of only 0,21 W/m<sup>2</sup>K
- LED Lighting with motion detector
- High quality room elements, made in Germany
- Interior completely stainless steel
- Exterior service accessibility
- Room Elements: Galvanized sheet steel, polyester coated, white, similar to RAL 9010, interior surfaces in stainless steel, 4 inch / 100 mm PU foam U value 0,21W/m<sup>2</sup>K

### **Floor:**

Floor overlay is chrome-nickel steel, pattern-rolled 5WL

### **Surface load:**

50.000 N/m<sup>2</sup>