

## HL 105 Three-way mixing valve training panel

Order code: **5201.06510500**



Information about product price on demand

Parameters

Quantitative unit

ks

### **GUNT HL 105**

Training panel is designed for practical learning about heating systems and plumbing.

It features a three-way mixing valve (DN 20), a circulating pump, and four rotameters for flow measurement.

Additionally, it includes four bimetallic thermometers for temperature monitoring and two heating water connections (DN 15) along with two boiler water connections (DN 15).

A differential pressure overflow valve ensures safe operation.

The system uses quick-release couplings for easy water connections.

## Technical Data & Specifications

- **Pump:**
  - Power consumption: 70W
  - Maximum flow rate: 60L/min
  - Maximum head: 4m
- **Three-Way Mixing Valve:**
  - Setting angle: 90°
  - Opening time: 100s

### Measuring Ranges

- **Flow Rate:**
  - 3x 150...1700L/h
  - 1x 40...400L/h
- **Temperature:** 0...100°C

### Power Supply

- 230V, 50Hz, 1 phase
- 230V, 60Hz, 1 phase

### Dimensions & Weight

- **LxWxH:** 1650x700x1850mm
- **Weight:** ~112kg

### Required for Operation

- Hot water supply: 1800L/h
- Cold water connection
- Drain