

**KB PRO 1060 Cooling incubator with an
extended temperature range**
Order code: **2103.90200437**



Cena bez DPH	22.566,00 Eur
Price with VAT	27.304,86 Eur

Parameters

Volume	1070l
Temperature range	-20°C...+100°C
Brand, Manufacturer	Binder
Number of shelves	2
Internal dimensions (wxdxh)	1011 × 847 × 1250
Quantitative unit	ks

- Temperature range: -20°C to +100°C
- Proven APT.line™ preheating chamber technology

- Energy-efficient cooling with modern inverter cooling unit
- Cooling with climate-neutral R-290 refrigerant
- Door heating to prevent condensation
- Adjustable fan speed
- Housing design with HIT technology
- Stainless-steel inner chamber
- Inner doors made of metal oxide-coated safety glass
- Two racks with stainless-steel telescopic rails
- Large access port with silicone plug
- Floor-standing units featuring robust twin casters with brakes at the front
- Stackable tabletop units with a volume of up to 130 liters
- Intuitive touchscreen controller with time-segment and real-time programming
- Ergonomically adjustable control terminal (for units with a volume of 470 liters and above)
- Signal triangle with light-up status display (for units with a volume of 470 liters and above)
- Internal data logger, measured values can be read out in open format via USB
- Class 3.3 independent temperature safety device (DIN 12880) with visual and acoustic alarms
- Unit self-test for comprehensive status analysis
- Data interfaces: Ethernet, USB BINDER Multi Management Software APT-COM™ basic edition
- Optional light modules for ICH photostability testing (for models 260, 470, 720)
- Optional LED light modules for plant growth (for models from 260)