

HELAGO-CZ, s.r.o. Commercial Register maintained by the Regional Court in Hradec Section C, File 17879 Kladská 1082 500 03 Hradec Králové 3 Company ID: 25 96 39 61, VAT: CZ 25963961 Phone: 495 220 229, 495 220 394

Fax: 495 220 154 GSM gate: 602 123 096 E-mail: info@helago-cz.cz Web: http://www.helago-cz.cz

KBF 1060 Constant climate chamber

Order code: 2103.90200482



Cena bez DPH 25.902,00 Eur Price with VAT 31.341,42 Eur

Parameters

Volume

Temperature range

Brand, Manufacturer

Number of shelves

Internal dimensions (w×d×h)

Quantitative unit

• Temperature range: 0°C to +70°C • Humidity range: 10% to 80% RH

1070l l

0°C...+70°C

Binder

2

1011 × 847 × 1250

ks

- Proven APT.line[™] preheating chamber technology
- Up to 40% lower energy consumption compared to the previous model
- Energy-efficient cooling with modern inverter cooling unit
- Cooling with climate-neutral R-600a refrigerant
- Door heating to prevent condensation
- Adjustable fan speed Humidity regulation with capacitive humidity sensor and responsive steam humidification
- Housing design with HIT technology
- Stainless-steel inner chamber
- Inner doors made of metal oxide-coated safety glass
- Two racks made of stainless steel
- Large access port with silicone plug
- Floor-standing units featuring robust twin casters with brakes at the front
- Intuitive touchscreen controller with time-segment and real-time programming
- Ergonomically adjustable control terminal
- Signal triangle with light-up status display Internal data logger, measured values can be read out in open format via USB
- Class 3.3 independent temperature safety device (DIN 12880) with visual and acoustic alarms
- Unit self-test for comprehensive status analysis
- Data interfaces: Ethernet, USB BINDER Multi Management Software APT-COM™ basic edition
- Optional LED light modules for plant growth (for models from 260)